St. Louis TMIP Model Review

East-West Gateway Council of Governments

December 7, 2006



Purpose of the Meeting

- TMIP Peer Review
- Panelists

Chandra Bhat — UT

David Boyce — Prof. Emeritus UIC

Frank Spielberg—VHB

Guy Rousseau — ARC

Ken Cervenka — NCTCOG (Chair)



Intended Model Uses

- Satisfy Federal Mandates
- Transportation Improvement Plan (TIP)
- Long Range Plan
- Air Quality Analysis
- Motor Vehicle Emission Budget -SIP Budget
- Corridor Analysis and Sub-area Studies
- Impact of Transit Alternatives
- Toll and HOV Lanes Analysis



Agenda for Today

8:45 AM Introduction

• 9:00 AM Purpose of the Meeting

9:15 AM Introduction & Background

• 9:30 AM Land Use & Demographic Forecasting

• 9:45 AM Household Interview Survey

• 10:00 AM Transportation Network Development

10:30 AM BREAK

• 10:45 AM Big Picture Issues: Validation

• 12:00 PM Lunch

1:00 PM Model Structure and Description

• 5:00 PM Adjourn




Agenda for 8th December


- 8:15 AM Continental Breakfast
- 8:45 AM Follow-up on Model Discussion
- 10:00 AM Closed Door Panel Discussion
- 12:00 PM Lunch
- 1:00 PM Panel Recommendations and Open Discussion
- 3:00 PM Adjourn



East-West Gateway -- Planning Area



East-West Gateway -- Planning Area



Some Statistics

- 3.89 trips per capita
- 2.51 person per HH
- 1.22 workers per HH
- 1.69 vehicles per HH
- 8.59 vehicle trips per HH
- 9.76 person trips per HH
- Mean Trip Duration: 17.87 minutes
- Mean Work Trip Duration: 22.57 minutes
- 18,514 Roadway Miles
- 21.58 Daily Vehicle Miles Traveled per capita

Source: NuStats



Comparative Metro Areas

	St. Louis (EWGCC)	Anchorage (AMATS)	PHILADELPHIA (DVRPC)	Knoxville (KUA MPO)	Columbus (MORPC)
Total Persons	2,482,935	260,283	6,188,463	687,249	1,540,157
Total Households	968,533	95,080	2,321,679	281,514	610,895
Year of Survey	2002	2002	2000	2000	1999
Household Size	2.5	2.6	2.4	2.4	2.5
Household Vehicles	1.7	2.0	1.6	1.8	1.7
Person Trip Rate	3.89	4.1	3.5	3.8	3.8
Household Trip Rate	9.8	10.3	8.1	8.2	9.5

Council of Governments

Source: NuStats

Existing Model

- Existing Model Developed in Early 1980, in MINUTP
- 1,066 and 43 External Stations
- Small Sample Survey—1990
- Revalidated—1997
- Cube Application Manager—2003



Background

- SAFETY-LU Legislative Changes, USEPA
- Model Improvement Plan
- 2002 HIS NuStats
- 2002 On-Board Passenger Survey
- Census Data



Background

- 2003 RFP
- Dec 2003 PB Consult Awarded Contract
- Jan 2004 Start Date
- PB Model Development on-going for Three Years
- TMIP Model Validation and Reasonableness Checking Manual
- Model is Still Not Validated



Charge to the Panelists


- Comment on the Sufficiency of the Model
- Identify Probable Causes of Problems and Potential Solutions
- Comment on Use of K-Factors
- Enhancements Short and Long Term




Topics


- The Region: Geography and Trends
- Land Use Allocation Model (LUAM)
- LUAM Forecasts
- Future Direction: Gateway Blueprint Model









TAZ Acreage: Frequency Distribution



TAZ 2000 Population Frequency Distribution



TAZ 2000 Employment Frequency Distribution



Land Use Allocation Model (LUAM)

Step 1: County-Level Forecasts

- Cohort Survival Model-No Migration
- Adjust based on
 - Expert Surveys
 - Current Development Plans
- This yields "control totals" for each county



LUAM: County Level Forecasts

	2000	2002	2005	2010	2015	2020	2025	2030	2035
St. Louis City	348,189	339,473	326,400	310,000	314,500	317,400	323,100	327,400	331,500
St. Louis County	1,016,315	1,017,029	1,018,100	1,021,800	1,020,900	1,016,200	1,008,700	1,004,200	999,700
St. Charles County	283,883	296,090	314,400	344,700	364,800	385,000	397,200	408,000	421,900
Jefferson County	198,099	202,859	210,000	224,700	233,600	245,400	255,500	263,800	272,100
Franklin County	93,807	95,764	98,700	106,900	116,800	125,500	135,000	144,400	15,400
Missouri Subtotal	1,940,293	1,951,216	1,967,600	2,008,100	2,050,600	2,089,500	2,119,500	2,147,800	2,040,600
Madison County	258,941	261,325	264,900	271,500	278,600	285,900	293,100	300,300	307,500
St. Clair County	256,082	257,689	260,100	265,800	270,600	274,300	279,600	284,100	288,600
Monroe County	27,619	28,611	30,100	32,400	34,200	35,500	36,900	38,300	39,700
Illinois Subtotal	542,642	547,625	555,100	569,700	283,400	595,700	609,600	622,700	635,800
Region	2,482,935	2,498,841	2,522,700	2,577,800	2,634,000	2,685,200	2,729,100	2,770,500	2,676,400

Land Use Allocation Model Step 2: Attractiveness Scores

Development attractiveness is a function of:

- Developable Land
- Proximity to "Attractors," e.g.
 - Interstate Ramps
 - Major Intersections
 - Employment Centers
 - Cultural Centers



Land Use Allocation Model Step 3: Allocation

- Account for known development activity
 - Geocode ongoing projects by TAZ
 - Subtract expected development from control totals
- Allocate adjusted control totals using attractiveness scores
- Assume current residential/commercial density to avoid exceeding amount of developable land
- This yields population forecasts by TAZ



A Note on Employment Forecasts


- County-level forecasts
 - Growth Trends
 - Holding Capacity
 - Development Outlook and Potential


- Employment Categories:
 - Employment = Retail + Non-Retail Employment
 - Non-Retail Employment = Basic + Service Employment


Rates of Change: Historic and Forecast


				Annual Compound Percent Growth		
	1990	2000	2035	1990-2000	2000-2035	
Population	2,389,616	2,482,942	2,814,819	0.38%	0.36%	
Households	904,743	968,262	1,238,536	0.68%	0.71%	
Employment	1,140,182	1,303,584	1,494,129	1.35%	0.39%	
Population Density (per mi ²)	533	553	627	0.37%	0.36%	
Employment Density (per mi ²)	254	291	333	1.37%	0.39%	












Future Directions: the Land Use Evolution and Assessment Model (LEAM)

- Developed at University of Illinois Urbana-Champaign (UIUC) Department of Urban Planning.
- Partners with National Center for Supercomputing at UIUC.
- Suite of Models: Economic, Demographic, Fiscal
- Simulates Land Use Change
- Developed Blueprint Model for EWGCOG



How does LEAM work?



PROBABILITY OF LAND-USE CHANGE



Creating Solutions Across Jurisdictional Boundaries

Integrating Land-Use and Transportation Models

Land-Use Feedback Congestion
Change


 Central Assumption: Probability of development decreases in congested areas, pushing developmental pressure to adjacent areas.

(Contributes to "Leapfrog" Development)


- Retail is an exception: Attracted to Congestion.
- Modeling Principles:
 - Congestion_t = f(Land-Use_t)
 - Land Use_{t+1} = f(Congestion_t + X)



Static Free-Flow Land-Use Change



Static Congested Land-Use Change



Household Interview Survey

- Survey Universe = All Households with a Telephone in the 8 County St. Louis Region.
- Personal 24 hr Travel Journals Recorded from April-May and September- December 2002.
- Weekdays Only




Household Interview Survey

- 5,094 Households
- 11,490 Persons
- 10,218 Vehicles
- 46,909 Unlinked Trips



Geographic Distribution of Sampled Households



Key Household Statistics

(Expanded)

	·		
Variable	St. Louis Region		
Total Households	968,533		
Total Persons	2,428,730		
Persons per HH	2.51		
Total Workers	1,173,772		
Workers per HH	1.22		
Total Vehicles	1,637,553		
Vehicles per HH	1.69		




Key Trip Statistics (Expanded)

Variable	St. Louis Region
Total Person Trips3	9,457,294
Mean Trips per HH	9.76
Mean Trips per Person	3.89
Mean Trip Duration (minutes)	17.87
Mean Work Trip Duration (minutes)	22.57
Total Vehicle Trips4	8,316,427
Total Transit Trips5	150,495
Total School bus Trips	422,319
Total Non-motorized Trips6	553,310




Mode of Travel for Daily Person Trips






Usual Mode To Main Job





Mode of Travel by Home County




Source: NuStats

EAST-WEST GATEWAY
Council of Governments


Creating Solutions Across Jurisdictional Boundaries

Main Mode of Trip to Work by **Vehicle Ownership**






Trip Distribution by Departure Hour






Starting Hour for Trips to Work






Starting Hour for Trips From Work





Summarized Trip Purposes





Trip Origins and Destinations AM Peak By County

County	Trip Origins	%	Trip Destinations	%
St. Louis County	533,370	39.0	547,362	40.0
St. Louis City	189,220	13.8	266,272	19.4
St. Charles County	159,020	11.6	131,516	9.6
St. Clair County	151,638	11.1	135,644	9.9
Madison County	138,840	10.1	120,132	8.8
Jefferson County	112,322	8.2	80,282	5.9
Franklin County	61,951	4.5	55,532	4.1
Monroe County	18,657	1.4	16,852	1.2
Out of Area	4,279	0.3	15,704	1.1
Total	1,369,297	100.0	1,369,297	100.0



Trip Origins and Destinations PM Peak By County

County	Trip Origins		Trip Destinations	%
St. Louis County	930,504	42.5	956,953	44.5
St. Louis City	297,846	13.6	284,716	13.2
St. Charles County	241,663	11.0	229,352	10.7
St. Clair County	231,409	10.6	234,693	10.9
Madison County	223,525	10.2	206,659	9.4
Jefferson County	148,717	6.8	125,782	5.7
Franklin County	72,183	3.3	68,482	3.1
Monroe County	22,575	1.0	19,034	0.9
Out of Area	20,794	0.9	26,763	1.2
Total	2,240,815	100.0	2,240,815	100.0



Trips by Household Size

Household (HH) Size	# HHs	Percent	# Trips	Percent	Trips/HH
1	268,090	27.7	1,072,887	11.3	4.00
2	308,670	31.9	2,417,433	25.6	7.83
3	160,997	16.6	1,838,116	19.4	11.42
4	138,538	14.3	2,245,794	23.7	16.21
5	62,211	6.4	1,186,788	12.5	19.08
6	20,209	2.1	481,137	5.1	23.81
7+	9,818	1.0	215,139	2.3	21.91
Total	968,533	100.0	9,457,294	100.0	9.76



Trips by Number of HH Workers

Workers	# HHs	%	# Trips	#Trips %	
0	233,176	24.1	1,226,755	13.0	5.26
1	372,953	38.5	3,367,128	35.6	9.03
2	300,040	31.0	3,812,254	40.3	12.71
3+	62,363	6.4	1,051,156	11.1	16.86
Total	968,533	100.0	9,457,293	100.0	9.76




Trips by Household Income

HH Income	#HHs	Percent	# Trips	Percent	Trips/HH
Less than \$4,999	22,393	2.3	105,249	1.3	4.70
\$5,000 to \$14,999	59,556	6.1	275,027	3.3	4.62
\$15,000 to \$24,999	98,710	10.2	693,757	8.4	7.03
\$25,000 to \$44,999	206,898	21.4	1,660,601	20.1	8.03
\$45,0000 to \$74,999	231,330	23.9	2,597,017	31.5	11.23
\$75,0000 or more	215,905	22.3	2,910,747	35.3	13.48
Missing	133,742	13.8			
Total	968,534	100.0	8,242,398	100.0	9.76




- Survey of All Fixed Route Transit Service
- March-April 2002
- •15,321 Surveys Returned From Adult Passengers (16+)
- •68% Response Rate
- •13,535 Bus
- •1,786 LRT



































Transportation Networks: Topics

- Highway Network
 - > Revised on 2002
- Transportation Analysis Zone
 - ➤ Redefined on 2002
- Area Type Model
 - ➤ New Effort






St. Louis MO-IL: 2002 Highway Network

TEval Model Highway Network includes all roadway functionally classified as Collector and up.





Highway Network: Statistics


- 25,565 Links (Plus 14,916 C . C)
 - > 14,352 Non Directional Links (Plus 7,464 C.C)
- 2,527 Centroids and 68 External Stations
 - > 5.75 Centroid Connectors (C.C) per TAZ
- Roadway Mileage
 - > 8,144 Center Line Miles
 - ➤ 18,509 Lane Miles
- 1,974 Count Location
 - ➤ 14% of the Roadway Link have Counts




Network Statistics: Contd.

- Average Free Flow Speed 39 mph
- Two Major Sub-Regional Movements








Highway Network: Development

- Network Data Base
 - ➤ Based on Tiger Shape Files
 - ➤ Model Uses *.Net Format (CUBE)
 - ➤ Maintain Network in both Formats
 - ➤ Can Import/Export into Shape Files
- Network Checks
 - Representation and Connectivity
 - ➤ Network Input Variables
 - > Collected Variables
 - > Estimated Variables




St. Louis MO-IL 2002 Free Flow Time Contour





Network Checks: Dangling Links



_FLAG=1 & FCLASS!=11; Dangling Links



Highway Network: Input Variable

- Collected Variables
 - ➤ Posted Speed Limit (maximum 70 mph)
 - > Number of Lanes
 - ➤ Distance
 - > Turn Prohibitions
 - > AADT



Highway Network: Input Variable

- Estimated Variables
 - > Centroid Connector Distance
 - ➤ Local Roadway Grids- Source Data
 - ➤ Equal C.C Distance within a TAZ
 - ✓ Network Loading
 - ✓ Local Roadway VMT
 - ✓ On an Average One Half to One Third of the Distance to the Centroid
- Major Issue:
 - > Tedious Manual Process




St. Louis MO-IL: 2002 Highway Network

Centroid Connectors are based on the local road way grid inside the TAZ. All Centroid Connectors within a TAZ have the same link distance.









Estimated Variable Contd. Lane Capacity

- Lane Capacity (Hourly and Period)
 - ➤ Changes with Change in Land-use
 - ➤ Level of Service E
 - ➤ Based on HCM 2000 Design Criteria
 - ➤ Combination of Network Variables
 - ➤ Roadway Functional Class, Area Type
 - ➤ Posted Speed, Number of Lanes

Basic Criteria for Capacity Calculation: Example Table

Fclass		Area Type	Posted Speed		Total Lane	Capacity	Remarks
			Lower Limit	Upper Limit		(Volume/Hr)	
3	Principle Arterial	Rural			>2	1400	Multi lane Hwy
3	5.5	Rural			= 2	1200	Two Lane Two Way
		_					
3	9.9	CBD	45			1000	
3	,,	Other Urban	45			1300	
3	3.3	CBD	40	45		900	
3	3.3	Other Urban	40	45		1200	
3	5.5	CBD	30	40		800	
3	5.5	Other Urban	30	40		1100	
3	5.5	CBD		30		700	
3	5.5	Other Urban		30		1000	




Lane Capacity: Peak Period

- Peak Period Capacity
 - ➤ Based on HIS "Time in Motion" Duration
 - ➤ Replicates Peak Hour Congestion for the Peak Period
 - ➤ Adjustment Factor in Assignment
- Major Issue: Bottlenecks Capacity

Example Table: Peak Period Capacity for the Intersate

Time Period	Lane Capacity	Lane	Total Hours	Peak Factor	Total Lin	k Capcity (Vehicle/ Period)	Adj Ratio
	(Vehicle/ Hour)		(Hours)		Unadjusted	Peak Period Adjusted	
Morning Peak (6 to 9 A.M.)	2,100	3	3	0.423	18,900	14,894	0.79
Mid Day (9 A.M. to 2 P.M.)	2,100	3	5	0.224	31,500	28,125	0.89
PM Peak (2 to 7 P.M.)	2,100	3	5	0.237	31,500	26,582	0.84
Night Time (7 P.M. to 6 A.M.)	2,100	3	11	0.272	69,300	23,162	0.33


Traffic Analysis Zones



St. Louis MO-IL: Previous Transportation Analysis Zone

Traffic Analysis Zones are based the Census Block Bounday, landuse of the area, roadway demarcation and access to the highway network. There are 1398 TAZs.

Legend







TAZ: Development

- **Boundary Revision Criteria**
 - > Census Block Boundary
 - ➤ Land Use
 - Access to the Road
 - Roadway Network
- Major Issue: Census Data Suppression Policy
- TAZ Statistics
 - ➤ Minimum Area 0.0025 Sq Miles
 - ➤ Maximum Area 34.08 Sq Miles

Region	Number of TAZ	Average Area Per TAZ (Sq Miles)
MO	1710	1.62
L	817	2.21
Regional	2527	1.81








TAZ Development: Districts

- Thirty Five Districts
 - ➤ Model Output Summary
 - > Reasonableness Checks Only
 - ➤ Not for Calibration









Model Area Type: Development


- Six Types of Area Definition
 - Rural, Suburban, Urban, Core, Business and Entertainment and CDB
- Criteria
 - > Population Density
 - Employment Density
 - Considers Adjacent TAZ
 - ➤ Range Determination (Iterative Process)
- Used for Model Calibration




Area Type Definition Chart












2002 Base Year Transit Network

- •82 Local Buses
- •20 Express Buses
- •1 Light Rail Line


- Peak Period 6-9 am
 - •268 One Way Lines Coded
- Off Peak Period 9am-2pm
 - •212 One Way Lines Coded



2002 Base Year Transit Network



2006 And Future Year Transit Network



- Transit Modes
 - Local Bus
 - Express Bus
 - Light Rail
 - Future Mode Place Holder



Transit Fares

- ·2002
 - •Local, Express, LRT =\$1.25
 - •Transfer= \$0.25
- ·2006
 - •Local, Express =\$1.75, \$2.25
 - •LRT=\$2.00, \$2.25

During Path Building, Each Path Segment is Assigned a Fare Based on Mode.



Transit Skims

Grouped by Period, Access Mode, and Mode Group

Mode Groups

Local Bus

Local Bus→Express Bus

Local→Express→LRT



Bus Headway=

(Time Difference between First and Last Bus within Period)

(Number of Buses-1)

• Example:

3 Peak Period Buses 6, 6:30, 7:30
(90 Minutes) = 45 min/bus
(2 buses)



Bus Travel Time

- Transit Speed is a Function of Congested Link Speed
- •Transit Speed Functions Differ by Link Functional Class
- •Functions Account for Boarding, Alighting, and Dwell Time



- Light Rail Headway 2002
 - •7.5 Minutes Peak
 - •15 Minutes Off-Peak
- Light Rail Travel Time & Speed
 - •Travel Time Hard Coded in Transit Line



Walk Access/Egress Support Links for Bus

- Generated Automatically in TRNBUILD
- Limit of 5 Links from Each Zone to Each Mode
- •Walk Speed is Set to 3 mph



- Walk Access/Egress Support Links for Bus
 - Walk Access Skims
 - •Walk Access and Egress Limited to 0.5 Mile
 - Drive Access Skims
 - •Walk Egress Limited to 1 Mile



Walk Transfer Support Links for Bus

- Generated Automatically in TRNBUILD
- •Link Distance Limited to 0.1 Mile
- •Consecutive Walk Transfers Limited to 0.25 Mile or 5 min

Support Links for LRT


•Read-in Text Files Contain LRT Access/Egress and Transfer Links



Park and Ride Support Links

- •Read-in Text Files Contain PNR Nodes
- •Files are Separated by Mode
- •PNR Links Created Automatically in TRNBUILD
- •Drive Access Links are Limited to 15 Miles or 30 min





- Modal Perceived Time Factors
 - •Local Bus= 1
 - •Express Bus=0.9 for Skim or 1 Otherwise
 - •LRT=0.9 for Skim or 1 Otherwise



Modal Perceived Time Factors

•Walk Access/Egress and Transfer= 2

•Drive Access/Egress= 1



Wait Time= ½ The Headway of a Transit Line

Perceived Wait Time Factors

- Initial Wait Time= 1.0
- Transfer Wait Time= 3

Actual Wait Time Minimum and Maximum

- Initial Wait Time= 2-60 Min
- •Transfer Wait Time= 1-60 Min



Transit Penalties

- •Boarding Penalty= 3 min
- Transfer Penalty=0 min for Transfer to LRT6 min for Other
- •Perceived Transfer Penalty Factor = 3

Transit Skims Output Matrix

- Total Transit IVT and IVT for Target Mode
- Initial and Transfer Wait Times
- •Walk or Drive Access/Egress Time
- Transfer Time
- •# of Transfers
- •# of Boardings
- Total Travel Time
- Walk Distance
- •Fare



Transit Accessibility Measures

Accessibility Ratio

Jobs/ FF Transit Time

Accessibility Matrix

Product of % of Zone within 0.25 Mile Buffer of Transit Stop for each I-J Pair



Big Picture: Validation Issues

W



Validation

- Overview of Model (this afternoon)
 - Structure, data development, estimation, calibration
 - Advanced practice trip-based model
- Frame the validation issues
- Identify
 - possible sources of problems
 - further investigations
 - Acceptable criteria
 - adjustments either model and/or data



Two Major Validation Issues

- Highway Volume-Count Validation
 - Interstate Crossings model high
 - Freeways
 - Generally somewhat low
 - Localized sections big discrepancies (I-64)
- Transit Mode Choice
 - Too strong Alternative Specific Constants
 - LRT positive
 - Bus negative
 - HBO (Off-peak skims) largest ASCs




Validation Reporting Available

- Vehicle volumes, transit boardings, congested speeds
- Revenue VMT: average bus speed compared to reported
- RMSE's and "percent errors" by facility type
- RMSE's and "percent errors" for the 35 districts
- Screen line and cordon line "percent errors" For those links with observed speed info, compare the average model output road speeds by functional class against the observed
- Total bus revenue miles and revenue hours statistics from Metro and how the overall average speed compares with the average peak and off-peak bus speeds in your model
- Summarize regional VMT by time-of-day and facility type, and compare the distribution of VMT against the HIS data, and some other data that I will provide to you within a few days
- Regional versus observed weekday route boardings by modes=4 & 7, the RMSE's for the bus routes
- Modeled versus observed weekday rail station boardings, the RMSE for boardings.



Daily Estimated Flows





Yr2002 Link Volumes

Facility Type	Average Volume	Count	VMT	VHT
Freeway	20,652	2,364	27,536,330	592,796
Expressway	21,551	319	3,382,173	76,474
Principal Arterial	10,640	5,170	13,304,674	423,492
Minor Arterial	4,520	6,773	7,841,290	250,379
Major Collector	1,903	9,219	5,244,126	180,553
Minor Collector	438	710	322,351	7,880
Local	703	909	317,066	11,003
Cent conn.	944	14,916	4,435,210	221,807
All	4,301	40,432	62,383,219	1,764,383



VMT/VHT by Time of Day

		Per	iod	
	AM	MD	PM	NT
VMT	11,171	17,997	24,447	8,768
VHT	311	475	765	213
Speed	36	38	32	41

VMT and VHT in thousands




AM Speeds


Facility Type	FreeFlow	Congested	Pct change
Freeway	62	50	-19%
Expressway	59	53	-10%
Arterial	39	33	-15%
Collector	36	32	-11%



AM Peak Period Speeds



AM Peak Period Speed




EAST-WEST GATEWAY
Council of Governments
Creating Solutions Across Jurisdictional Boundaries


AM Peak Speeds

>50% low 50-20% low 20-10% low Within 10%

10-20% high 20-50% high >50% high




RMSE by Facility Type



Overall PRMSE = 43.2%




RMSE by Volume Group






Obs vs. Est Counts



Count/Est Map



>50% low

50-20% low

20-10% low

Within 10%


10-20% high

20-50% high

>50% high



Obs/Est Comparison, Core



>50% low

50-20% low

20-10% low

Within 10%


10-20% high

20-50% high

>50% high




Count/Est by District




Obs/Est Link Distribution

Observed vs. Estimated Link Volume



Obs/Est Link Distribution

Est vs. Observed Link Volume




Creating Solutions Across Jurisdictional Boundaries

SME Test Results

- Synthetic Matrix Estimation
- Used Modeled V-T table as a base
- Used daily counts split by time, class
- 9% increase in vehicle-trips required after 10 iterations



SME PRMSE



Overall SME PRMSE=30%



Mode Choice Calibration

Rail Constant

– HBW: +0.74 (25.3% Mkt Share of HBW Transit)

» 30 min

– HBO: +3.05 (26.4% Mkt Share of HBO Transit)

» 203 min

NHB: +1.66 (28.8% Mkt Share of NHB Transit)

» 111 min

Potential Problems:

- Transit Rail Skims Not Competitive?
- Off-Peak Times Not Representative?
- Rail Access adequate?
- Bus Times Too Fast?
- Trip Distribution?



Target Shares (%)

		Purpose	
Mode	HBW	НВО	NHB
Auto	94.6	93.3	93.4
NM	2.1	5.9	5.8
Local	2.3	0.6	0.6
Express	0.2		
Rail	0.8	0.2	0.2




Other Constants


- HBO Drive-Transit constant=+7.5 (Mkt Share 16% of all HBO transit)
- HBO Transit constant =-11.9
 (Mkt Share 0.8% of all HBO trips)



Walk-Rail Mode Shares to CBD




HBW Walk-LRT Shares to CBD





HBW Drive-LRT Shares to CBD



ATEWAY

Trip Generation-Steve Ruegg

- Tables that show the production and attraction rates for each purpose (or tour), and comparisons against info from other regions.
- Identify total regional distribution of trips by purpose and market segment.
- Under reporting
- Trip Purposes and Market Segmentation-avg trip rate and compare
- Asserted models (Truck, University, Airports)
- Special location (malls)
- Externals



Trip Rates by Purpose

-			
	per person	per hhld	per worker
WHBW	0.586	1.488	1.219
WHBO	0.157	0.399	0.327
WNHB	0.239	0.608	0.498
AWNHB	0.167	0.424	0.347
NWHBO	0.682	1.732	1.419
HBSHOP	0.702	1.782	1.460
NWNHB	0.554	1.408	1.153
HBK12	0.373	0.948	0.777
Work tour	0.983	2.496	2.045
At-Work tour	0.167	0.424	0.347
NW-tour	2.311	5.870	4.809
Chauffer	0.196	0.498	0.408
total	3.657	9.287	FASTO PEST Council of Government of Council of Covernment

Non-response Rate

- +11% overall
- Applied to NHB and HBO purposes
- Based on GPS sample



Asserted Models

- Airport Trips Mpls/St. Paul
 - Used split between hbo, wnhb, nwnhb
- College/Univ
 - Used NC State Data for resident and commuter generation
- Truck Used Tampa model



Mall attractors

 Mall indicator modified trip attractions for HBSHOP trips to regional mall zones



External Trips

- Based on external vehicle volumes
- Uses fixed shares for truck, through, work and non-work trips
- P/A based on home location



NW-NHB CBD Attractions


- Initially overestimated by factor of 20
- Adjusted for CBD attractions





Trip Distribution-Steve Ruegg


- Sample zone selection
- Show how the Generation-calculated attractions in the 2,500 zones compares to what was generated from the singlyconstrained distribution, aggregated to the District level, and provide the purposespecific information in a table (with ratios for Distribution-based attractions/Generationbased attractions).
- nw-nhb attraction rate alteration
- K factors application











K-Factors

- For attraction Area-Types
 - Urban, Core, CBD, OBD
- Intra-County
- Intra-Zone
- Inter-State




Mode Choice--Steve Ruegg

- Show the nesting structures and the coefficients for each market segment, and identify how the "relative weights" of the MC coefficients compare to the skimming weighs.
- logsums factors
- Coefficients/FTA Standards
- Have a table that shows the total person trips for each market segment, by mode; as well as a column that shows the regional percent transit share



Mode Choice Model Structure



MC and Path-Building Weights

Measure	Path-building	MC
Initial Wait Time	2.0	2.5-2.6
Xfer Wait	3.0	2.0-2.6
Walk Time	2.0	2.5-4.0



Model Coefficients

	HBW	НВО	NHB
IVT	-0.025	-0.0150	-0.0150
Initial Wait	-0.0625	-0.040	-0.040
Long Wait	-0.025	-0.030	-0.040
Xfer Wait	-0.050	-0.040	-0.040
Walk Access	-0.0625	-0.060	-0.060
Cost (\$)		-0.2150	-0.2050
Cost-Low	-0.5		
Cost-Med	-0.36		
Cost-High	-0.19		



HBW Modal Trip Shares

	HBW		
	Trips	Share	Est Share
DA	1,204,000	82.3%	81.5%
Shared Ride	180,000	12.3%	12.3%
Non-Motorized	31,000	2.1%	1.8%
Local Bus	34,000	2.3%	3.2%
Express Bus	2,000	0.1%	0.4%
MetroLink	12,000	0.8%	1.1%
Total	1,463,000	100.0%	100.0%

HBO Mode Shares

	HBO		
	Trips	Share	Est Share
DA	1,755,000	45.4%	46.7%
Shared Ride	1,849,000	47.9%	47.8%
Non-Motorized	228,000	5.9%	4.6%
Local Bus	23,000	0.6%	0.7%
Express Bus	100	<0.1%	<0.1%
MetroLink	8,000	0.2%	0.3%
Total	3,862,000	100.0%	1000%

NHB Mode Shares

	NHB		
	Trips	Share	Est Share
DA	1,336,000	55.5%	57.8%
Shared Ride	913,000	37.9%	36.4%
Non-Motorized	140,000	5.8%	4.8%
Local Bus	13,000	0.5%	0.6%
Express Bus	100	<0.1%	<0.1%
MetroLink	5,000	0.2%	0.3%
Total	2,408,000	100.0%	100.6%

Feedback Loop

- Feedback criteria
- Based on D to D trip table and link times, compared to prev iteration
 - RMSF < 10%
 - Or >90% of links/cells vary by <10%
- Current default to 2 feedback iterations




Assignment-Steve Ruegg

- Show the VDFs in graph format
- Identify the vehicle classes used
- Costs
- Moving from purposes to TOD
- Time of the day, periods and peak hour factors
- Convergence and Convergence Criteria for assignment, show how and why—how stable things have gotten and why we choose 19 iterations. There was a graph that showed the VMT and VDT fluctuation between iterations
- Counts and HMPS




VDF for Hwy Assignments





Bus Speed Functions

Bus Transit Time Functions




Vehicle Classes

- SOV
- HOV (user-defined, default 2+)
- Truck



Diurnal Factors


EWGW Diurnal Factors





P->A factors

EWG P->A Factors






Period Definitions

- AM Peak 6am-9am 42.3% in highest hr
- MD 9am-2pm 22.4% in highest hr
- PM Peak 2pm-7pm, 23.7% in highest hr
- NT 7pm-6am 27.3% in highes hr




Assignment Convergence





Assignment Convergence

AM Assignment, Convergence





Questions



Computation Time

Type	# of Computers	Process	Time/Iteration (hr:min:sec)
Intra	1	Mode Choice/Destination Choice-Calibration Run	24:00:00
Intra	3	Mode Choice/Destination Choice-Calibration Run	08:26:50
Intra	6	Mode Choice/Destination Choice-Calibration Run	07:39:40
Intra	4	Convert Trip tables from MC/DC to Hourly	00:40:30
Intra	6	Convert Trip tables from MC/DC to Hourly	00:31:05
Intra & Multistep	1	Assignment AM	02:15:00
Intra & Multistep	2	Assignment AM	01:10:03
Intra & Multistep	4	Assignment AM	00:53:36
Intra	1	Hourly to Period Trip Tables	00:07:01
Intra	5	Hourly to Period Trip Tables	EAST-WEST (00:08:10 Council of Gove Creating Solutions Across Juri

Questions

